

电梯/扶梯信号控制电缆

Flexible Control Cable (Escalator&Elevator)

RVV

产品标准 (Product Standard): JB/T 8734.3

型号 Type	规格mm ² Specification	导体结构 Conductor Structure	电缆外径下限 Min. diameter (mm)	电缆外径上限 Max. diameter (mm)	额定电压 +U ₀ /U(V)	20℃时导体直流电阻 20℃ conductor DCR (Ω/KM)	70℃时绝缘电阻最小值 70℃ Min.insulation resistance (MΩ/KM)
RVV	6×0.75	30/0.18	6.5	9.6	300/500	≤26	0.011
RVV	7×0.75	30/0.18	6.5	9.6	300/500	≤26	0.011
RVV	8×0.75	30/0.18	7.5	10.6	300/500	≤26	0.011
RVV	10×0.75	30/0.18	9	13.2	300/500	≤26	0.011
RVV	12×0.75	30/0.18	9.5	13.2	300/500	≤26	0.011
RVV	15×0.75	30/0.18	10.7	14	300/500	≤26	0.011
RVV	16×0.75	30/0.18	10.7	14	300/500	≤26	0.011
RVV	19×0.75	30/0.18	11.3	15	300/500	≤26	0.011
RVV	20×0.75	30/0.18	11.6	15.5	300/500	≤26	0.011
RVV	24×0.75	30/0.18	13.5	17	300/500	≤26	0.011
RVV	25×0.75	30/0.18	13.6	17.1	300/500	≤26	0.011
RVV	30×0.75	30/0.18	14.3	19.5	300/500	≤26	0.011
RVV	37×0.75	30/0.18	15.5	21.6	300/500	≤26	0.011
RVV	40×0.75	30/0.18	16.2	21.8	300/500	≤26	0.011
RVV	6×1	32/0.2	8.7	11	300/500	≤19.5	0.01
RVV	7×1	32/0.2	8.7	11	300/500	≤19.5	0.01
RVV	8×1	32/0.2	9.8	13.2	300/500	≤19.5	0.01
RVV	10×1	32/0.2	11.7	14.5	300/500	≤19.5	0.01
RVV	12×1	32/0.2	11.9	14.8	300/500	≤19.5	0.01
RVV	15×1	32/0.2	11.6	15.5	300/500	≤19.5	0.01
RVV	16×1	32/0.2	11.6	15.5	300/500	≤19.5	0.01
RVV	19×1	32/0.2	14.1	17.8	300/500	≤19.5	0.01
RVV	20×1	32/0.2	14.6	18.3	300/500	≤19.5	0.01
RVV	24×1	32/0.2	16.8	20.5	300/500	≤19.5	0.01
RVV	25×1	32/0.2	17	20.8	300/500	≤19.5	0.01
RVV	30×1	32/0.2	18.1	22.6	300/500	≤19.5	0.01
RVV	37×1	32/0.2	19	23	300/500	≤19.5	0.01
RVV	40×1	32/0.2	20.6	25.5	300/500	≤19.5	0.01
RVV	2×0.75+1×2.0	32/0.2 38/0.26	6.3	8.5	300/500	≤19.5/10.2	0.011/0.009
RVV	5×0.75+1×2.0	32/0.2 38/0.26	7.7	9.8	300/500	≤19.5/10.2	0.011/0.009
RVV	6×0.75+1×2.0	32/0.2 38/0.26	8	11	300/500	≤19.5/10.2	0.011/0.009
RVV	7×0.75+1×2.0	32/0.2 38/0.26	8.4	11.5	300/500	≤19.5/10.2	0.011/0.009
RVV	11×0.75+1×2.0	32/0.2 38/0.26	9.5	14.2	300/500	≤19.5/10.2	0.011/0.009
RVV	12×0.75+1×2.0	32/0.2 38/0.26	9.7	14.5	300/500	≤19.5/10.2	0.011/0.009
RVV	18×0.75+1×2.0	32/0.2 38/0.26	12.2	15.5	300/500	≤19.5/10.2	0.011/0.009
RVV	19×0.75+1×2.0	32/0.2 38/0.26	12.8	16	300/500	≤19.5/10.2	0.011/0.009
RVV	24×0.75+1×2.0	32/0.2 38/0.26	14	18.8	300/500	≤19.5/10.2	0.011/0.009
RVV	29×0.75+1×2.0	32/0.2 38/0.26	14.5	19.5	300/500	≤19.5/10.2	0.011/0.009
RVV	36×0.75+1×2.0	32/0.2 38/0.26	15.8	22	300/500	≤19.5/10.2	0.011/0.009
RVV	6×1.5	48/0.2	9.9	13.3	300/500	≤13.3	0.01
RVV	8×1.5	48/0.2	10.8	14.2	300/500	≤13.3	0.01
RVV	10×1.5	48/0.2	13.5	16.7	300/500	≤13.3	0.01
RVV	6×2.5	47/0.26	12.4	15.8	300/500	≤7.98	0.009
RVV	8×2.5	47/0.26	14.5	16.5	300/500	≤7.98	0.009
RVV	10×2.5	47/0.26	16.2	20	300/500	≤7.98	0.009