

电梯随行电缆-高提升高度

Flat Traveling Cable for High Rise Elevator

TVVB

产品标准 (Product Standard): JB/T 8734.6

型号 Type	规格mm ² Specification	导体结构 Conductor Structure	成品最大直径 Diameter.(mm)	额定电压 +U ₀ /U(V)	20°C时导体直流电阻 20°C conductor DCR (Ω/KM)
TVVBG	30×0.75	30/0.18	8.4×48.4	300/500	≤26
TVVBG	36×0.75	30/0.18	9.0×52	300/500	≤26
TVVBG	40×0.75	30/0.18	8.4×60.8	300/500	≤26
TVVBG	42×0.75	30/0.18	9.0×52	300/500	≤26
TVVBG	48×0.75	30/0.18	9.0×64	300/500	≤26
TVVBG	54×0.75	30/0.18	9.0×72	300/500	≤26
TVVBG	60×0.75	30/0.18	9.0×78.2	300/500	≤26
TVVBG-TV	2×1+75-5	40/0.18	8.6×23.5	300/500	≤19.5
TVVBG-TV	12×0.75+75-5	30/0.18	9.0×32.5	300/500	≤26
TVVBG-TV	20×0.75+75-5	30/0.18	8.6×43.5	300/500	≤26
TVVBG-TV	24×0.75+75-5	30/0.18	9.0×49.7	300/500	≤26
TVVBPG-TV(铜网屏蔽)	2×2P×0.75+75-5	30/0.18	9.0×31.5	300/500	≤26
TVVBPG-TV(铜网屏蔽)	6×2P×0.75+75-5	30/0.18	9.0×47	300/500	≤26
TVVBPG-TV(铜网屏蔽)	8×2P×0.75+75-5	30/0.18	9.0×55.3	300/500	≤26
TVVBPG(铜网屏蔽)	30×0.75+2×2P×0.75	30/0.18	9.0×60	300/500	≤26
TVVBPG(铜网屏蔽)	36×0.75+2×2P×0.75	30/0.18	9.0×64	300/500	≤26
TVVBPG(铜网屏蔽)	40×0.75+2×2P×0.75	30/0.18	9.0×71.2	300/500	≤26
TVVBPG(铜网屏蔽)	42×0.75+2×2P×0.75	30/0.18	9.0×70	300/500	≤26
TVVBPG(铜网屏蔽)	56×0.75+2×2P×0.75	30/0.18	9.0×82	300/500	≤26
TVVBPG-TV(铜网屏蔽)	30×0.75+2×2P×0.75+75-5	30/0.18	9.0×66.4	300/500	≤26
TVVBPG-TV(铜网屏蔽)	36×0.75+2×2P×0.75+75-5	30/0.18	9.0×70	300/500	≤26
TVVBPG-TV(铜网屏蔽)	40×0.75+2×2P×0.75+75-5	30/0.18	9.0×77.2	300/500	≤26
TVVBPG(铝箔屏蔽)	24×0.75+2×2P×0.75+1×2	30/0.18 38/0.25	9.8×54.6	300/500	≤26/10.2
TVVBPG-TV(铝箔屏蔽)	24×0.75+2×2P×0.75+75-5	30/0.18	9.0×59.8	300/500	≤26
TVVBPG-TV(铜网屏蔽)	30×0.75+2×2P×0.75+1×2+75-5	30/0.18 38/0.25	9.0×66.2	300/500	≤26/10.2
TVVBPG-TV(铜网屏蔽)	36×0.75+2×2P×0.75+75-5	30/0.18	9.0×71.8	300/500	≤26
TVVBPG-TV(铜网屏蔽)	40×0.75+2×2P×0.75+1×2+75-5	30/0.18 38/0.25	9.0×77.7	300/500	≤26/10.2
TVVBPG-TV(半导电屏蔽)	36×0.75+2×2P×0.75+1×2+75-5	30/0.18 38/0.25	9.0×70.6	300/500	≤26/10.2
TVVBPG-TV(半导电屏蔽)	48×0.75+2×2P×0.75+75-5	30/0.18	9.0×81.8	300/500	≤26
TVVBPG(半导电屏蔽)	42×0.75+2×2P×0.75	30/0.18	9.0×69.8	300/500	≤26
TVVBPG(半导电屏蔽)	48×0.75+2×2P×0.75	30/0.18	9.0×75.8	300/500	≤26
TVVBPG(半导电屏蔽)	56×0.75+2×2P×0.75	30/0.18	9.0×81.8	300/500W	≤26
TVVBPG(半导电屏蔽)	60×0.75+2×2P×0.75	30/0.18	9.0×90	300/500	≤26