

电梯/扶梯控制柜电缆

Control Box Wire(Escalator&Elevator)

产品标准 (Product Standard):GB/T 5023.3

型号 Type	规格mm ² Specification	导体结构 Conductor Structure	电缆外径下限 Min. diameter (mm)	电缆外径上限 Max.diameter (mm)	额定电压 +U ₀ /U(V)	20℃时导体直流电阻 20℃ conductor DCR (Ω/KM)	70℃时绝缘电阻最小值 70℃ Min.insulation resistance (MΩ/KM)
60227 IEC 05(BV)	0.5	1/0.8	1.9	2.3	300/500	≤36	0.015
60227 IEC 05(BV)	0.75	1/0.98	2.1	2.5	300/500	≤24.5	0.012
60227 IEC 05(BV)	1	1/1.13	2.2	2.7	300/500	≤18.1	0.011
60227 IEC 01(BV)	1.5	1/1.38	2.6	3.2	450/750	≤12.1	0.011
60227 IEC 01(BV)	2.5	7/0.68	3.3	4	450/750	≤7.41	0.0009
60227 IEC 01(BV)	4	7/0.86	3.8	4.6	450/750	≤4.61	0.0077
60227 IEC 01(BV)	6	7/1.04	4.3	5.2	450/750	≤3.08	0.0065
60227 IEC 01(BV)	10	7/1.35	5.6	6.7	450/750	≤1.83	0.0065
60227 IEC 01(BV)	16	7/1.7	6.4	7.8	450/750	≤1.15	0.005
60227 IEC 01(BV)	25	7/2.14	8.1	9.7	450/750	≤0.727	0.005
60227 IEC 01(BV)	35	7/2.52	9	10.9	450/750	≤0.524	0.0043
60227 IEC 01(BV)	50	19/1.78	10.6	12.8	450/750	≤0.387	0.0043
60227 IEC 01(BV)	70	19/2.16	12.1	14.6	450/750	≤0.268	0.0035
60227 IEC 01(BV)	95	19/2.52	14.1	17.1	450/750	≤0.193	0.0035
60227 IEC 06(RV)	0.5	28/0.15	2.1	2.5	300/500	≤39	0.013
60227 IEC 06(RV)	0.75	30/0.18	2.2	2.7	300/500	≤26	0.011
60227 IEC 06(RV)	1	40/0.18	2.4	2.8	300/500	≤19.5	0.01
60227 IEC 02(RV)	1.5	48/0.2	2.8	3.4	450/750	≤13.3	0.01
60227 IEC 02(RV)	2.5	47/0.26	3.4	4.1	450/750	≤7.98	0.009
60227 IEC 02(RV)	4	77/0.26	3.9	4.8	450/750	≤4.95	0.007
60227 IEC 02(RV)	6	112/0.26	4.4	5.3	450/750	≤3.3	0.006
60227 IEC 02(RV)	10	88/0.38	5.7	6.8	450/750	≤1.91	0.0056
60227 IEC 02(RV)	16	141/0.38	6.7	8.1	450/750	≤1.21	0.0046
60227 IEC 02(RV)	25	220/0.38	8.4	10.2	450/750	≤0.78	0.0044
60227 IEC 02(RV)	35	308/0.38	9.7	11.7	450/750	≤0.554	0.0038
60227 IEC 02(RV)	50	441/0.38	11.5	13.9	450/750	≤0.386	0.0037
60227 IEC 02(RV)	70	421/0.46	13.2	16	450/750	≤0.272	0.0032

产品标准 (Product Standard):JB/T 8734.2

型号 Type	规格mm ² Specification	导体结构 Conductor Structure	电缆外径下限 Min. diameter (mm)	电缆外径上限 Max.diameter (mm)	额定电压 +U ₀ /U(V)	20℃时导体直流电阻 20℃ conductor DCR (Ω/KM)	70℃时绝缘电阻最小值 70℃ Min.insulation resistance (MΩ/KM)
BVR	0.75	7/0.37	/	2.9	450/750	≤24.5	0.013
BVR	1	7/0.43	/	3.1	450/750	≤18.1	0.012
BVR	1.5	7/0.52	/	3.4	450/750	≤12.1	0.011
BVR	2.5	19/0.41	/	4.1	450/750	≤7.41	0.011
BVR	4	19/0.52	/	4.8	450/750	≤4.61	0.009
BVR	6	19/0.64	/	5.3	450/750	≤3.08	0.0084
BVR	10	49/0.52	/	7.3	450/750	≤1.83	0.0072
BVR	16	49/0.64	/	8.6	450/750	≤1.15	0.0062
BVR	25	98/0.58	/	10.2	450/750	≤0.727	0.0058
BVR	35	133/0.58	/	11.7	450/750	≤0.524	0.0052
BVR	50	133/0.69	/	13.9	450/750	≤0.387	0.0051
BVR	70	189/0.69	/	16	450/750	≤0.268	0.0045