

# 电梯/扶梯动力电缆

## Power Cable (Escalator&Elevator)

RVV、VVR、VVRP

产品标准 (Product Standard): JB/T 8734.3

型号 Type	规格mm <sup>2</sup> Specification	导体结构 Conductor Structure	电缆外径下限 Min. diameter (mm)	电缆外径上限 Max. diameter (mm)	额定电压 +U <sub>0</sub> /U(V)	20℃时导体直流电阻 20℃ conductor DCR (Ω/KM)	70℃时绝缘电阻最小值 70℃ Min.insulation resistance (MΩ/KM)
RVV	2×6	112/0.26	12.5	14.5	300/500	≤3.3	0.008
RVV	2×10	78/0.4	14.1	17.3	300/500	≤1.91	0.0056
RVV	3×4	77/0.26	10.7	14	300/500	≤4.96	0.007
RVV	3×6	112/0.26	12	14.8	300/500	≤3.3	0.007
RVV	4×4	77/0.26	11.8	14.6	300/500	≤4.96	0.007
RVV	4×6	112/0.26	14	16	300/500	≤3.3	0.006
RVV	4×10	78/0.4	17.3	19	300/500	≤1.91	0.0056
RVV	5×4	77/0.26	13.3	16.5	300/500	≤4.96	0.007
RVV	5×6	112/0.26	15.3	17.5	300/500	≤3.3	0.006
RVV	7×6	112/0.26	16.5	20.1	300/500	≤3.3	0.006
RVV	7×10	78/0.4	20.7	25.5	300/500	≤1.91	0.0056
VVR	5×16	301/0.26	22	26.9	0.6/1KV	≤1.21	0.0046
VVR	7×4	77/0.26	15.5	19.4	0.6/1KV	≤4.96	0.007
VVR	7×6	112/0.26	17.5	21.4	0.6/1KV	≤3.3	0.006
VVR	7×10	78/0.4	21.9	26.8	0.6/1KV	≤1.91	0.0056
VVR	7×16	301/0.26	24.3	30.3	0.6/1KV	≤1.21	0.0046
VVR	3×6+1×4	112/0.26、77/0.26	14.4	17.6	0.6/1KV	≤3.3/4.96	0.006/0.007
VVR	3×10+1×6	78/0.4、112/0.26	16.9	20.7	0.6/1KV	≤1.91/3.3	0.0056/0.007
VVR	3×16+1×10	301/0.26、78/0.4	20.3	24.9	0.6/1KV	≤1.21/1.91	0.0046/0.0056
VVRP	2×4	77/0.26	11.7	14.3	0.6/1KV	≤4.96	0.007
VVRP	2×6	112/0.26	18.5	22.5	0.6/1KV	≤3.3	0.006
VVRP	3×4	77/0.26	12.2	15	0.6/1KV	≤4.96	0.007
VVRP	3×6	112/0.26	13.7	16.7	0.6/1KV	≤3.3	0.006
VVRP	3×10	78/0.4	16.6	20.2	0.6/1KV	≤1.91	0.0056
VVRP	4×4	77/0.26	13.5	15.6	0.6/1KV	≤4.96	0.007
VVRP	4×6	112/0.26	15	18.4	0.6/1KV	≤3.3	0.006
VVRP	4×10	78/0.4	18	22	0.6/1KV	≤1.91	0.0056
VVRP	4×16	301/0.26	20.7	25.3	0.6/1KV	≤1.21	0.0046
VVRP	5×6	112/0.26	16.3	20.1	0.6/1KV	≤3.3	0.006
VVRP	5×10	78/0.4	19.8	24.2	0.6/1KV	≤1.91	0.0056
VVRP	7×4	77/0.26	16	20	0.6/1KV	≤4.96	0.007
VVRP	7×6	112/0.26	18	22	0.6/1KV	≤3.3	0.006
VVRP	7×10	78/0.4	22	27	0.6/1KV	≤1.91	0.0056
VVRP	7×16	301/0.26	27.3	33.3	0.6/1KV	≤1.21	0.0046