

电梯/扶梯信号控制电缆

Flexible Control Cable (Escalator&Elevator)

RVVP、RVVPS

产品标准 (Product Standard): JB/T 8734.5

型号 Type	规格mm ² Specification	导体结构 Conductor Structure	电缆外径下限 Min. diameter (mm)	电缆外径上限 Max. diameter (mm)	额定电压 +U ₀ /U(V)	20℃时导体直流电阻 20℃ conductor DCR (Ω/KM)	70℃时绝缘电阻最小值 70℃ Min.insulation resistance (MΩ/KM)
RVVP	2×0.3	16/0.15	4.8	6.2	300/300	≤69.2	0.014
RVVP	2×0.4	23/0.15	5.1	6.5	300/300	≤48.2	0.013
RVVP	2×0.5	28/0.15	5.3	6.8	300/300	≤39	0.012
RVVP	2×0.75	30/0.18	5.8	7.4	300/300	≤26	0.01
RVVP	2×1	40/0.18	6.4	8.2	300/300	≤19.5	0.01
RVVP	2×1.5	48/0.2	7.3	9.2	300/300	≤13.3	0.009
RVVP	2×2.5	47/0.26	8.5	10.5	300/300	≤7.98	0.009
RVVP	3×0.3	16/0.15	5.1	6.5	300/300	≤69.2	0.014
RVVP	3×0.4	23/0.15	5.4	6.9	300/300	≤48.2	0.013
RVVP	3×0.5	28/0.15	5.6	7.1	300/300	≤39	0.012
RVVP	3×0.75	30/0.18	6.1	7.8	300/300	≤26	0.01
RVVP	3×1	40/0.18	7.2	9.1	300/300	≤19.5	0.01
RVVP	3×1.5	48/0.2	8	10	300/300	≤13.3	0.009
RVVP	3×2.5	47/0.26	9.1	11.1	300/300	≤7.98	0.009
RVVP	4×0.3	16/0.15	5.5	7	300/300	≤69.2	0.014
RVVP	4×0.4	23/0.15	5.9	7.5	300/300	≤48.2	0.013
RVVP	4×0.5	28/0.15	5.8	7.8	300/300	≤39	0.013
RVVP	4×0.75	30/0.18	6.1	8.1	300/300	≤26	0.011
RVVP	4×1	40/0.18	7.4	9.4	300/300	≤19.5	0.01
RVVP	4×1.5	48/0.2	8	10	300/300	≤13.3	0.01
RVVP	4×2.5	47/0.26	10.2	12.2	300/300	≤7.98	0.009
RVVP	5×0.3	16/0.15	6	7.6	300/300	≤69.2	0.014
RVVP	5×0.4	23/0.15	6.4	8.1	300/300	≤48.2	0.013
RVVP	5×0.5	28/0.15	6.2	8.2	300/300	≤39	0.013
RVVP	5×0.75	30/0.18	6.6	8.6	300/300	≤26	0.011
RVVP	5×1	40/0.18	8	10	300/300	≤19.5	0.01
RVVP	5×1.5	48/0.2	9.1	11.1	300/300	≤13.3	0.01
RVVP	5×2.5	47/0.26	11.7	13.7	300/300	≤7.98	0.009
RVVP	6×0.3	16/0.15	6.5	8.2	300/300	≤69.2	0.014
RVVP	6×0.4	23/0.15	7.3	9.2	300/300	≤48.2	0.013
RVVP	6×0.5	28/0.15	7	9	300/300	≤39	0.013
RVVP	6×0.75	30/0.18	7.5	9.5	300/300	≤26	0.011
RVVP	6×1	40/0.18	9	11	300/300	≤19.5	0.01
RVVP	6×1.5	48/0.2	10	12	300/300	≤13.3	0.01
RVVP	6×2.5	47/0.26	13	15	300/300	≤7.98	0.009
RVVP	7×0.3	16/0.15	6.5	8.2	300/300	≤69.2	0.014
RVVP	7×0.4	23/0.15	7.3	9.2	300/300	≤48.2	0.013
RVVP	7×0.5	28/0.15	7.3	9.3	300/300	≤39	0.013
RVVP	7×0.75	30/0.18	8.5	10.3	300/300	≤26	0.011
RVVP	7×1	40/0.18	10.2	12.2	300/300	≤19.5	0.01
RVVP	7×1.5	48/0.2	11	13	300/300	≤13.3	0.01
RVVP	7×2.5	47/0.26	14	16.2	300/300	≤4.95	0.009
RVVPS	2×2×0.5	28/0.15	6.8	8.8	300/300	≤39	0.013
RVVPS	2×2×0.75	30/0.18	7.4	9.4	300/300	≤26	0.01
RVVPS	2×2×1	40/0.18	8.4	10.4	300/300	≤19.5	0.01
RVVPS	2×2×1.5	48/0.2	8.8	10.8	300/300	≤13.3	0.009
RVVPS	2×2×2.5	47/0.26	10.8	12.8	300/300	≤4.95	0.009