

电梯/扶梯信号控制电缆

Flexible Control Cable (Escalator&Elevator)

AVR、AVVR

产品标准 (Product Standard): JB/T 8734.4

型号 Type	规格mm ² Specification	导体结构 Conductor Structure	电缆外径下限 Min. diameter (mm)	电缆外径上限 Max. diameter (mm)	额定电压 +U ₀ /U(V)	20℃时导体直流电阻 20℃ conductor DCR (Ω/KM)	70℃时绝缘电阻最小值 70℃ Min.insulation resistance (MΩ/KM)
AVR	1×0.2	12/0.15	/	1.6	300/300	≤92.3	0.014
AVR	1×0.3	16/0.15	/	2	300/300	≤69.2	0.014
AVR	1×0.4	23/0.15	/	2.1	300/300	≤48.2	0.012
AVVR	2×0.2	12/0.15	3.6	4.7	300/300	≤92.3	0.014
AVVR	2×0.3	16/0.15	4.1	5.3	300/300	≤69.2	0.014
AVVR	2×0.4	23/0.15	4.4	5.7	300/300	≤48.2	0.013
AVVR	3×0.2	12/0.15	3.8	4.9	300/300	≤92.3	0.014
AVVR	3×0.3	16/0.15	4.4	5.7	300/300	≤69.2	0.014
AVVR	3×0.4	23/0.15	4.7	6	300/300	≤48.2	0.013
AVVR	4×0.2	12/0.15	4.2	5.4	300/300	≤92.3	0.014
AVVR	4×0.3	16/0.15	4.8	6.2	300/300	≤69.2	0.014
AVVR	4×0.4	23/0.15	5.1	6.6	300/300	≤48.2	0.013
AVVR	5×0.2	12/0.15	4.5	5.8	300/300	≤92.3	0.014
AVVR	5×0.3	16/0.15	5.3	6.7	300/300	≤69.2	0.014
AVVR	5×0.4	23/0.15	5.6	7.2	300/300	≤48.2	0.013
AVVR	(6、7)×0.2	12/0.15	4.9	6.3	300/300	≤92.3	0.014
AVVR	(6、7)×0.3	16/0.15	5.7	7.3	300/300	≤69.2	0.014
AVVR	(6、7)×0.4	23/0.15	6.2	7.8	300/300	≤48.2	0.013
AVVR	8×0.2	12/0.15	5.6	7.2	300/300	≤92.3	0.014
AVVR	8×0.3	16/0.15	6.5	8.2	300/300	≤69.2	0.014
AVVR	8×0.4	23/0.15	7	8.6	300/300	≤48.2	0.013
AVVR	9×0.2	12/0.15	6	7.6	300/300	≤92.3	0.014
AVVR	9×0.3	16/0.15	7.2	9	300/300	≤69.2	0.014
AVVR	9×0.4	23/0.15	7.8	9.2	300/300	≤48.2	0.013
AVVR	10×0.2	12/0.15	6.3	8	300/300	≤92.3	0.014
AVVR	10×0.3	16/0.15	7.8	9.7	300/300	≤69.2	0.014
AVVR	10×0.4	23/0.15	8.3	10.4	300/300	≤48.2	0.013
AVVR	12×0.2	12/0.15	6.5	8.2	300/300	≤92.3	0.014
AVVR	12×0.3	16/0.15	8	10.1	300/300	≤69.2	0.014
AVVR	12×0.4	23/0.15	8.6	10.8	300/300	≤48.2	0.013
AVVR	14×0.2	12/0.15	7.2	9.1	300/300	≤92.3	0.014
AVVR	14×0.3	16/0.15	8.4	10.6	300/300	≤69.2	0.014
AVVR	14×0.4	23/0.15	9.1	11.3	300/300	≤48.2	0.013
AVVR	16×0.2	12/0.15	7.6	9.6	300/300	≤92.3	0.014
AVVR	16×0.3	16/0.15	8.9	11.1	300/300	≤69.2	0.014
AVVR	16×0.4	23/0.15	9.6	11.9	300/300	≤48.2	0.013
AVVR	18×0.2	12/0.15	8.6	10	300/300	≤92.3	0.014
AVVR	18×0.3	16/0.15	9.5	11	300/300	≤69.2	0.014
AVVR	18×0.4	23/0.15	10.5	11.6	300/300	≤48.2	0.013
AVVR	19×0.2	12/0.15	8.1	10.1	300/300	≤92.3	0.014
AVVR	19×0.3	16/0.15	9.4	11.7	300/300	≤69.2	0.014
AVVR	19×0.4	23/0.15	10.1	12.6	300/300	≤48.2	0.013